Technical data


6007LLU/LP03

Single row deep groove ball bearings



Deep groove ball bearing, radial contact, pressed steel cage, contact seals on both sides

Visual(s)



Product definition

d	35 mm
D	62 mm
B	14 mm
rs min	1 mm
Radial clearance class	CN
Mass	0.16 kg
Brand	NTN

Product performance

Dynamic load, C	16 kN
Static load, C0	10.3 kN
Fatigue limit load, Cu	0.47 kN
f0	14.8
Nlim (grease)	5,700 Tr/min
Min operating temperature, Tmin	-20 °C
Max operating temperature, Tmax	60 °C
Characteristic cage frequency, FTF	0.42 Hz
Characteristic rolling element frequency, BSF	5.95 Hz
Characteristic outer ring frequency, BPF0	4.6 Hz
Characteristic inner ring frequency, BPFI	6.4 Hz

Abutment dimensions

da min	40 mm
da max	42 mm
Da max	57 mm
ra max	1 mm

Calculation factors

Equivalent dynamic radial load

P = X.Fr + Y.Fa

$\frac{f_0 F_a}{C_0}$	e	Fa / Fr ≤ e		Fa / Fr > e	
		X	Y	X	Y
0.172	0.19	1	0	0.56	2.3
0.345	0.22				1.99
0.689	0.26				1.71
1.03	0.28				1.55
1.38	0.3				1.45
2.07	0.34				1.31
3.45	0.38				1.15
5.17	0.42				1.04
6.89	0.44				1

Equivalent static radial load

Po = Xo.Fr + Yo.Fa

X_0	Y_0
0.6	0.5

For single or DT bearing arrangement :

If Po <Fr, then use Po = Fr