
Technical data


6313.ZC3

Single row deep groove ball bearings



Deep groove ball bearing, radial contact, pressed steel cage, shield on one side

Visual(s)



Product definition

d	65 mm
D	140 mm
B	33 mm
d1	82.2 mm
D1	123.7 mm
rs min	2.1 mm
Radial clearance class	C3
Mass	2.08 kg
Brand	SNR

Product performance

Dynamic load, C	92.4 kN
Static load, C0	59.8 kN
Fatigue limit load, Cu	2.7 kN
f0	13.2
Nref	6,400 Tr/min
Nlim	8,100 Tr/min
Min operating temperature, Tmin	-40 °C
Max operating temperature, Tmax	120 °C
Characteristic cage frequency, FTF	0.38 Hz
Characteristic rolling element frequency, BSF	4.07 Hz
Characteristic outer ring frequency, BPF0	3.07 Hz
Characteristic inner ring frequency, BPFI	4.93 Hz

Abutment dimensions

da min	76 mm
da max	82.2 mm
Ce min	0 mm
Da max	129 mm
ra max	2 mm

Calculation factors

Equivalent dynamic radial load

P = X.Fr + Y.Fa

$\frac{f_0 F_a}{C_0}$	e	Fa / Fr ≤ e		Fa / Fr > e	
		X	Y	X	Y
0.172	0.19	1	0	0.56	2.3
0.345	0.22				1.99
0.689	0.26				1.71
1.03	0.28				1.55
1.38	0.3				1.45
2.07	0.34				1.31
3.45	0.38				1.15
5.17	0.42				1.04
6.89	0.44				1

Equivalent static radial load

Po = Xo.Fr + Yo.Fa

X_0	Y_0
0.6	0.5

For single or DT bearing arrangement :

If Po <Fr, then use Po = Fr