Technical data


22212EAKW33ZZ


Double row spherical roller bearings

ULTAGE



Visual(s)





Product definition

d	60 mm
D	110 mm
B	28 mm
d2	71.9 mm
D1	98.5 mm
rs min	1.5 mm
Number of lubrication holes	3
b	6.9 mm
k	3 mm
Associated sleeve reference	H312
e	0.24
Y1	2.84
Y2	4.23
Y0	2.78
Radial clearance class	CN
Mass	1.17 kg
Brand	SNR

Product performance

Dynamic load, C	187 kN
Static load, C0	181 kN
Fatigue limit load, Cu	22 kN
Nref	5,600 Tr/min
Nlim	7,500 Tr/min
Min operating temperature, Tmin	-40 °C
Max operating temperature, Tmax	200 °C
Characteristic cage frequency, FTF	0.42 Hz
Characteristic rolling element frequency, BSF	6.17 Hz
Characteristic outer ring frequency, BPF0	7.6 Hz
Characteristic inner ring frequency, BPFI	10.4 Hz

Abutment dimensions

da min	69 mm
da max	1.5 mm
db min	65 mm
Ce min	9 mm
Da max	101 mm
ra max	1.5 mm

Calculation factors

Equivalent dynamic radial load

$P = X.Fr + Y.Fa$

$Fa/Fr \leq e$		$Fa/Fr > e$	
X	Y	X	Y
1	Y1	0.67	Y2

Equivalent static radial load

$Po = Xo.Fr + Yo.Fa$

X_0	Y_0
1	Y0

The values for e, Y1, Y2 and Y0 are shown in the above table .