Technical data


22217EAW33ZZC3


Double row spherical roller bearings

ULTAGE



Visual(s)





Product definition

d	85 mm
D	150 mm
B	36 mm
d2	100.7 mm
D1	136.5 mm
rs min	2 mm
Number of lubrication holes	3
b	7.9 mm
k	3.5 mm
Associated sleeve reference	P0
e	0.22
Y1	3.07
Y2	4.58
Y0	3.01
Radial clearance class	C3
Mass	2.64 kg
Brand	SNR

Product performance

Dynamic load, C	324 kN
Static load, C0	330 kN
Fatigue limit load, Cu	38.7 kN
Nref	4,100 Tr/min
Nlim	5,400 Tr/min
Min operating temperature, Tmin	-40 °C
Max operating temperature, Tmax	200 °C
Characteristic cage frequency, FTF	0.42 Hz
Characteristic rolling element frequency, BSF	6.37 Hz
Characteristic outer ring frequency, BPF0	7.63 Hz
Characteristic inner ring frequency, BPFI	10.37 Hz

Abutment dimensions

da min	96 mm
da max	2 mm
db min	100.7 mm
Da max	139 mm
ra max	2 mm

Calculation factors

Equivalent dynamic radial load

$P = X.Fr + Y.Fa$

Fa / Fr ≤ e		Fa / Fr > e	
X	Y	X	Y
1	Y1	0.67	Y2

Equivalent static radial load

$P_0 = X_0.Fr + Y_0.Fa$

X_0	Y_0
1	Y0

The values for e, Y1, Y2 and Y0 are shown in the above table .