Technical data


22220EAKW33ZZ


Double row spherical roller bearings

ULTAGE



Visual(s)





Product definition

d	100 mm
D	180 mm
B	46 mm
d2	118.2 mm
D1	160.8 mm
rs min	2.1 mm
Number of lubrication holes	3
b	11.2 mm
k	5 mm
Associated sleeve reference	H320
e	0.24
Y1	2.84
Y2	4.23
Y0	2.78
Radial clearance class	CN
Mass	4.94 kg
Brand	SNR

Product performance

Dynamic load, C	472 kN
Static load, C0	495 kN
Fatigue limit load, Cu	52.6 kN
Nref	3,600 Tr/min
Nlim	4,600 Tr/min
Min operating temperature, Tmin	-40 °C
Max operating temperature, Tmax	200 °C
Characteristic cage frequency, FTF	0.42 Hz
Characteristic rolling element frequency, BSF	6.23 Hz
Characteristic outer ring frequency, BPF0	7.61 Hz
Characteristic inner ring frequency, BPFI	10.39 Hz

Abutment dimensions

da min	112 mm
da max	2 mm
db min	108 mm
Ce min	8 mm
Da max	168 mm
ra max	2 mm

Calculation factors

Equivalent dynamic radial load

$P = X.Fr + Y.Fa$

$Fa/Fr \leq e$		$Fa/Fr > e$	
X	Y	X	Y
1	Y1	0.67	Y2

Equivalent static radial load

$Po = Xo.Fr + Yo.Fa$

X_0	Y_0
1	Y0

The values for e, Y1, Y2 and Y0 are shown in the above table .