
Technical data


6007ZZNR/2AS

Single row deep groove ball bearings



Deep groove ball bearing, radial contact, pressed steel cage, snap ring & groove on outer diameter, shields on both sides

Visual(s)



Product definition

d	35 mm
D	62 mm
B	14 mm
a min	1.88 mm
a max	2.08 mm
Ca min	3.48 mm
Ca max	3.78 mm
rs min	1 mm
rNs min	0.5 mm
D3 max	59.61 mm
b min	1.9 mm
b max	2.2 mm
r0 max	0.6 mm
D4 max	67.7 mm
f	1.7 mm
Snap ring reference	R62
Radial clearance class	CN
Mass	0.16 kg
Brand	NTN

Product performance

Dynamic load, C	16 kN
Static load, C0	10.3 kN
Fatigue limit load, Cu	0.47 kN
f0	14.8
Nlim (grease)	12,000 Tr/min
Min operating temperature, Tmin	-20 °C
Max operating temperature, Tmax	120 °C
Characteristic cage frequency, FTF	0.42 Hz
Characteristic rolling element frequency, BSF	5.95 Hz
Characteristic outer ring frequency, BPF0	4.6 Hz
Characteristic inner ring frequency, BPFI	6.4 Hz

Abutment dimensions

da min	40 mm
Da max	57 mm
ra max	1 mm
rNa max	0.5 mm
Db min	68.5 mm

Calculation factors

Equivalent dynamic radial load

P = X.Fr + Y.Fa

$\frac{f_0 F_a}{C_0}$	e	Fa / Fr ≤ e		Fa / Fr > e	
		X	Y	X	Y
0.172	0.19	1	0	0.56	2.3
0.345	0.22				1.99
0.689	0.26				1.71
1.03	0.28				1.55
1.38	0.3				1.45
2.07	0.34				1.31
3.45	0.38				1.15
5.17	0.42				1.04
6.89	0.44				1

Equivalent static radial load

Po = Xo.Fr + Yo.Fa

X_0	Y_0
0.6	0.5

For single or DT bearing arrangement :

If Po <Fr, then use Po = Fr