
Technical data


6216.ZZC3

Single row deep groove ball bearings



Deep groove ball bearing, radial contact, pressed steel cage, shields on both sides

Visual(s)



Product definition

d	80 mm
D	140 mm
B	26 mm
d1	93.4 mm
D1	127.5 mm
rs min	2 mm
Radial clearance class	C3
Mass	1.42 kg
Brand	SNR

Product performance

Dynamic load, C	72.1 kN
Static load, C0	53 kN
Fatigue limit load, Cu	2.3 kN
f0	14.6
Nref	5,500 Tr/min
Nlim	6,000 Tr/min
Min operating temperature, Tmin	-25 °C
Max operating temperature, Tmax	120 °C
Characteristic cage frequency, FTF	0.41 Hz
Characteristic rolling element frequency, BSF	5.6 Hz
Characteristic outer ring frequency, BPF0	4.13 Hz
Characteristic inner ring frequency, BPFI	5.87 Hz

Abutment dimensions

da min	89 mm
da max	93.4 mm
Ce min	0 mm
Da max	131 mm
ra max	2 mm

Calculation factors

Equivalent dynamic radial load

P = X.Fr + Y.Fa

$\frac{f_0 F_a}{C_0}$	e	Fa / Fr ≤ e		Fa / Fr > e	
		X	Y	X	Y
0.172	0.19	1	0	0.56	2.3
0.345	0.22				1.99
0.689	0.26				1.71
1.03	0.28				1.55
1.38	0.3				1.45
2.07	0.34				1.31
3.45	0.38				1.15
5.17	0.42				1.04
6.89	0.44				1

Equivalent static radial load

Po = Xo.Fr + Yo.Fa

X_0	Y_0
0.6	0.5

For single or DT bearing arrangement :

If Po <Fr, then use Po = Fr