
Technical data


6412ZZ/5K

Single row deep groove ball bearings

Deep groove ball bearing, radial contact, pressed steel cage, shields on both sides



Visual(s)



Product definition

d	60 mm
D	150 mm
B	35 mm
rs min	2.1 mm
Radial clearance class	CN
Mass	2.77 kg
Brand	NTN

Product performance

Dynamic load, C	102 kN
Static load, C0	64.5 kN
Fatigue limit load, Cu	2.85 kN
f0	12.6
Nlim (grease)	4,800 Tr/min
Min operating temperature, Tmin	-20 °C
Max operating temperature, Tmax	120 °C
Characteristic cage frequency, FTF	0.37 Hz
Characteristic rolling element frequency, BSF	3.63 Hz
Characteristic outer ring frequency, BPF0	2.6 Hz
Characteristic inner ring frequency, BPFI	4.4 Hz

Abutment dimensions

da min	71 mm
Da max	139 mm
ra max	2 mm

Calculation factors

Equivalent dynamic radial load

P = X.Fr + Y.Fa

$\frac{f_0 F_a}{C_0}$	e	Fa / Fr ≤ e		Fa / Fr > e	
		X	Y	X	Y
0.172	0.19	1	0	0.56	2.3
0.345	0.22				1.99
0.689	0.26				1.71
1.03	0.28				1.55
1.38	0.3				1.45
2.07	0.34				1.31
3.45	0.38				1.15
5.17	0.42				1.04
6.89	0.44				1

Equivalent static radial load

Po = Xo.Fr + Yo.Fa

X_0	Y_0
0.6	0.5

For single or DT bearing arrangement :

If Po <Fr, then use Po = Fr