Technical data

22208.EAKW33


Double row spherical roller bearings



Spherical roller bearing, pressed steel cage, groove and lubrication holes on outer ring, tapered bore 1:12

ULTAGE

Visual(s)



Product definition

d	40 mm
D	80 mm
B	23 mm
d2	50.2 mm
D1	70.8 mm
rs min	1.1 mm
Number of lubrication holes	3
b	5.4 mm
k	2.5 mm
Associated sleeve reference	H308
e	0.27
Y1	2.47
Y2	3.68
Y0	2.41
Radial clearance class	CN
Mass	0.5 kg
Brand	SNR

Product performance

Dynamic load, C	116 kN
Static load, C0	105 kN
Fatigue limit load, Cu	11 kN
Nref	8,200 Tr/min
Nlim	11,000 Tr/min
Min operating temperature, Tmin	-40 °C
Max operating temperature, Tmax	200 °C
Characteristic cage frequency, FTF	0.42 Hz
Characteristic rolling element frequency, BSF	5.62 Hz
Characteristic outer ring frequency, BPF0	6.64 Hz
Characteristic inner ring frequency, BPFI	9.36 Hz

Abutment dimensions

da min	47 mm
da max	1 mm
db min	44 mm
Ce min	5 mm
Da max	73 mm
ra max	1 mm

Calculation factors

Equivalent dynamic radial load

$P = X.Fr + Y.Fa$

$Fa/Fr \leq e$		$Fa/Fr > e$	
X	Y	X	Y
1	Y1	0.67	Y2

Equivalent static radial load

$P_0 = X_0.Fr + Y_0.Fa$

X_0	Y_0
1	Y0

The values for e, Y1, Y2 and Y0 are shown in the above table .