Technical data


32024XU


Single row tapered roller bearings

Tapered roller bearing, pressed steel cage



Visual(s)





Product definition

d	120 mm
D	180 mm
B	38 mm
C	29 mm
T	38 mm
a	39 mm
rs min	2 mm
r1s min	2 mm
e	0.46
Y2	1.31
Y0	0.72
Mass	3.25 kg
ISO 355 reference	T4DC120
Brand	NTN

Product performance

Dynamic load, C	245 kN
Rating life coefficient, A2	1
Static load, C0	420 kN
Nlim (oil)	2,500 Tr/min
Nlim (grease)	1,800 Tr/min
Min operating temperature, Tmin	-40 °C
Max operating temperature, Tmax	120 °C

Abutment dimensions

da max	132 mm
db min	131 mm
Da max	170 mm
Db min	173 mm
ra max	2 mm
r1a max	2 mm

Calculation factors

Equivalent dynamic radial load

$P = X.Fr + Y.Fa$

Fa / Fr ≤ e		Fa / Fr > e	
X	Y	X	Y
1	0	0.4	Y2

Equivalent static radial load

$Po = Xo.Fr + Yo.Fa$

X_0	Y_0
0.5	Y0

If Po <Fr, then use Po = Fr

The values for e, Y2 and Y0 are shown in the above table