Technical data


32311U

Single row tapered roller bearings

Tapered roller bearing, pressed steel cage



Visual(s)



Product definition

d	55 mm
D	120 mm
B	43 mm
C	35 mm
T	45.5 mm
d1	85.5 mm
a	30.5 mm
rs min	2.5 mm
r1s min	2 mm
e	0.35
Y2	1.74
Y0	0.96
Mass	2.44 kg
ISO 355 reference	T2FD055
Brand	NTN

Product performance

Dynamic load, C	215 kN
Rating life coefficient, A2	1
Static load, C0	275 kN
Fatigue limit load, Cu	33.5 kN
Nlim (oil)	4,400 Tr/min
Nlim (grease)	3,300 Tr/min
Min operating temperature, Tmin	-40 °C
Max operating temperature, Tmax	120 °C
Characteristic cage frequency, FTF	0.41 Hz
Characteristic rolling element frequency, BSF	5.28 Hz
Characteristic outer ring frequency, BPF0	6.57 Hz
Characteristic inner ring frequency, BPFI	9.43 Hz

Abutment dimensions

da max	68 mm
db min	67 mm
Da min	99 mm
Da max	110 mm
Db min	111 mm
Ca min	4 mm
Cb min	10.5 mm
ra max	2 mm
r1a max	2 mm