Technical data


4T-30304


Single row tapered roller bearings



Tapered roller bearing, pressed steel cage

Visual(s)





Product definition

d	20 mm
D	52 mm
B	15 mm
C	13 mm
T	16.25 mm
d1	35 mm
a	11.5 mm
rs min	1.5 mm
r1s min	1.5 mm
e	0.3
Y2	2
Y0	1.1
Mass	0.17 kg
ISO 355 reference	T2FB020
Brand	NTN

Product performance

Dynamic load, C	35.5 kN
Rating life coefficient, A2	1.4
Static load, C0	34 kN
Nlim (oil)	11,000 Tr/min
Nlim (grease)	8,000 Tr/min
Min operating temperature, Tmin	-40 °C
Max operating temperature, Tmax	120 °C
Characteristic cage frequency, FTF	0.39 Hz
Characteristic rolling element frequency, BSF	4.43 Hz
Characteristic outer ring frequency, BPF0	5.12 Hz
Characteristic inner ring frequency, BPFI	7.88 Hz

Abutment dimensions

da max	28 mm
db min	28.5 mm
Da min	42.5 mm
Da max	43.5 mm
Db min	47 mm
Ca min	2 mm
Cb min	3 mm
ra max	1.5 mm
r1a max	1.5 mm

Calculation factors

Equivalent dynamic radial load

$P = X.Fr + Y.Fa$

$Fa / Fr \leq e$		$Fa / Fr > e$	
X	Y	X	Y
1	0	0.4	Y2

Equivalent static radial load

$Po = Xo.Fr + Yo.Fa$

X_0	Y_0
0.5	Y0

If $Po < Fr$, then use $Po = Fr$

The values for e, Y2 and Y0 are shown in the above table