Technical data


4T-30308D


Single row tapered roller bearings



Tapered roller bearing, pressed steel cage

Visual(s)





Product definition

d	40 mm
D	90 mm
B	23 mm
C	17 mm
T	25.25 mm
d1	67 mm
a	29.5 mm
rs min	2 mm
r1s min	1.5 mm
e	0.83
Y2	0.73
Y0	0.4
Mass	0.74 kg
ISO 355 reference	T7FB040
Brand	NTN

Product performance

Dynamic load, C	77 kN
Rating life coefficient, A2	1.4
Static load, C0	85.5 kN
Fatigue limit load, Cu	10.4 kN
Nlim (oil)	5,200 Tr/min
Nlim (grease)	3,900 Tr/min
Min operating temperature, Tmin	-40 °C
Max operating temperature, Tmax	120 °C
Characteristic cage frequency, FTF	0.42 Hz
Characteristic rolling element frequency, BSF	5.52 Hz
Characteristic outer ring frequency, BPF0	6.76 Hz
Characteristic inner ring frequency, BPFI	9.24 Hz

Abutment dimensions

da max	50 mm
db min	50 mm
Da min	71 mm
Da max	81.5 mm
Db min	86.5 mm
Ca min	3 mm
Cb min	8 mm
ra max	2 mm
r1a max	1.5 mm

Calculation factors

Equivalent dynamic radial load

$P = X.Fr + Y.Fa$

$Fa / Fr \leq e$		$Fa / Fr > e$	
X	Y	X	Y
1	0	0.4	Y2

Equivalent static radial load

$Po = Xo.Fr + Yo.Fa$

X_0	Y_0
0.5	Y0

If $Po < Fr$, then use $Po = Fr$

The values for e, Y2 and Y0 are shown in the above table