Technical data


4T-33262/33462

Single row tapered roller bearings



Tapered roller bearing, pressed steel cage

Visual(s)



Product definition

d	66.68 mm
D	117.48 mm
B	30.16 mm
C	23.81 mm
T	30.16 mm
a	27.6 mm
rs min	3.5 mm
r1s min	3.3 mm
e	0.44
Y2	1.38
Y0	0.76
Mass	1.36 kg
Brand	NTN

Product performance

Dynamic load, C	117 kN
Rating life coefficient, A2	1.4
Static load, C0	175 kN
Min operating temperature, Tmin	-40 °C
Max operating temperature, Tmax	120 °C
Characteristic cage frequency, FTF	0.45 Hz
Characteristic rolling element frequency, BSF	9.14 Hz
Characteristic outer ring frequency, BPF0	10.3 Hz
Characteristic inner ring frequency, BPFI	12.7 Hz

Abutment dimensions

ra max	3.5 mm
r1a max	3.3 mm

Calculation factors

Equivalent dynamic radial load

$P = X.Fr + Y.Fa$

$Fa / Fr \leq e$		$Fa / Fr > e$	
X	Y	X	Y
1	0	0.4	Y2

Equivalent static radial load

$Po = Xo.Fr + Yo.Fa$

X_0	Y_0
0.5	Y0

If $Po < Fr$, then use $Po = Fr$

The values for e, Y2 and Y0 are shown in the above table