Technical data


4T-420

Single row tapered roller bearings



Mounted cone, sheet metal cage

Visual(s)



Product definition

d	40 mm
B	29.08 mm
d1	59.5 mm
e	0.26
Y2	2.28
Y0	1.25
Brand	NTN

Product performance

Dynamic load, C	95.5 kN
Rating life coefficient, A2	1.4
Static load, C0	107 kN
Fatigue limit load, Cu	13 kN
Nlim (oil)	6,100 Tr/min
Nlim (grease)	4,600 Tr/min
Min operating temperature, Tmin	-40 °C
Max operating temperature, Tmax	120 °C
Characteristic cage frequency, FTF	0.41 Hz
Characteristic rolling element frequency, BSF	5.09 Hz
Characteristic outer ring frequency, BPF0	5.69 Hz
Characteristic inner ring frequency, BPFI	8.31 Hz

Abutment dimensions

ra max	3.5 mm

Calculation factors

Equivalent dynamic radial load

P = X.Fr + Y.Fa

Fa / Fr ≤ e		Fa / Fr > e	
X	Y	X	Y
1	0	0.4	Y2

Equivalent static radial load

Po= Xo.Fr + Yo.Fa

X_0	Y_0
0.5	Y0

If Po <Fr, then use Po = Fr

The values for e, Y2 and Y0 are shown in the above table