Technical data


4T-48286

Single row tapered roller bearings

Mounted cone, sheet metal cage



Visual(s)



Product definition

d	123.82 mm
B	38.1 mm
d1	155.5 mm
e	0.31
Y2	1.97
Y0	1.08
Brand	NTN

Product performance

Dynamic load, C	224 kN
Rating life coefficient, A2	1.4
Static load, C0	435 kN
Fatigue limit load, Cu	46.5 kN
Nlim (oil)	2,400 Tr/min
Nlim (grease)	1,800 Tr/min
Min operating temperature, Tmin	-40 °C
Max operating temperature, Tmax	120 °C
Characteristic cage frequency, FTF	0.46 Hz
Characteristic rolling element frequency, BSF	13.23 Hz
Characteristic outer ring frequency, BPF0	15.28 Hz
Characteristic inner ring frequency, BPFI	17.72 Hz

Abutment dimensions

ra max	3.5 mm

Calculation factors

Equivalent dynamic radial load

P = X.Fr + Y.Fa

Fa / Fr ≤ e		Fa / Fr > e	
X	Y	X	Y
1	0	0.4	Y2

Equivalent static radial load

Po= Xo.Fr + Yo.Fa

X_0	Y_0
0.5	Y0

If Po <Fr, then use Po = Fr

The values for e, Y2 and Y0 are shown in the above table