Technical data


4T-48393/48320

Single row tapered roller bearings

Tapered roller bearing, pressed steel cage



Visual(s)



Product definition

d	136.52 mm
D	190.5 mm
B	39.69 mm
C	33.34 mm
T	39.69 mm
d1	164.5 mm
a	35.69 mm
e	0.32
Y2	1.87
Y0	1.03
Mass	3.43 kg
Brand	NTN

Product performance

Dynamic load, C	236 kN
Rating life coefficient, A2	1.4
Static load, C0	475 kN
Fatigue limit load, Cu	50 kN
Nlim (oil)	2,300 Tr/min
Nlim (grease)	1,700 Tr/min
Min operating temperature, Tmin	-40 °C
Max operating temperature, Tmax	120 °C
Characteristic cage frequency, FTF	0.46 Hz
Characteristic rolling element frequency, BSF	13.95 Hz
Characteristic outer ring frequency, BPF0	16.74 Hz
Characteristic inner ring frequency, BPFI	19.26 Hz

Abutment dimensions

ra max	3.5 mm
r1a max	3.3 mm

Calculation factors

Equivalent dynamic radial load

$P = X.Fr + Y.Fa$

Fa / Fr ≤ e		Fa / Fr > e	
X	Y	X	Y
1	0	0.4	Y2

Equivalent static radial load

$Po = Xo.Fr + Yo.Fa$

X_0	Y_0
0.5	Y0

If Po <Fr, then use Po = Fr

The values for e, Y2 and Y0 are shown in the above table