Technical data


4T-JLM508748

Single row tapered roller bearings

Mounted cone, sheet metal cage



Visual(s)



Product definition

d	60 mm
B	24 mm
d1	78 mm
e	0.4
Y2	1.49
Y0	0.82
Brand	NTN

Product performance

Dynamic load, C	83 kN
Rating life coefficient, A2	1.4
Static load, C0	122 kN
Fatigue limit load, Cu	14.9 kN
Nlim (oil)	4,900 Tr/min
Nlim (grease)	3,700 Tr/min
Min operating temperature, Tmin	-40 °C
Max operating temperature, Tmax	120 °C
Characteristic cage frequency, FTF	0.45 Hz
Characteristic rolling element frequency, BSF	9.12 Hz
Characteristic outer ring frequency, BPF0	10.3 Hz
Characteristic inner ring frequency, BPFI	12.7 Hz

Abutment dimensions

ra max	5 mm

Calculation factors

Equivalent dynamic radial load

P = X.Fr + Y.Fa

Fa / Fr ≤ e		Fa / Fr > e	
X	Y	X	Y
1	0	0.4	Y2

Equivalent static radial load

Po= Xo.Fr + Yo.Fa

X_0	Y_0
0.5	Y0

If Po <Fr, then use Po = Fr

The values for e, Y2 and Y0 are shown in the above table