Technical data


4T-JM719149/JM719113

Single row tapered roller bearings



Tapered roller bearing, pressed steel cage

Visual(s)



Product definition

d	95 mm
D	150 mm
B	34 mm
C	27 mm
T	35 mm
d1	121.5 mm
a	33.3 mm
e	0.44
Y2	1.36
Y0	0.75
Mass	2.19 kg
Brand	NTN

Product performance

Dynamic load, C	180 kN
Rating life coefficient, A2	1.4
Static load, C0	279 kN
Fatigue limit load, Cu	32.1 kN
Nlim (oil)	3,100 Tr/min
Nlim (grease)	2,300 Tr/min
Min operating temperature, Tmin	-40 °C
Max operating temperature, Tmax	120 °C
Characteristic cage frequency, FTF	0.45 Hz
Characteristic rolling element frequency, BSF	9.18 Hz
Characteristic outer ring frequency, BPF0	10.76 Hz
Characteristic inner ring frequency, BPFI	13.24 Hz

Abutment dimensions

ra max	3 mm
r1a max	2.5 mm

Calculation factors

Equivalent dynamic radial load

$P = X.Fr + Y.Fa$

$Fa/Fr \leq e$		$Fa/Fr > e$	
X	Y	X	Y
1	0	0.4	Y2

Equivalent static radial load

$Po = Xo.Fr + Yo.Fa$

X_0	Y_0
0.5	Y0

If $Po < Fr$, then use $Po = Fr$

The values for e, Y2 and Y0 are shown in the above table