Technical data


6002LLUNRC3/2AS

Single row deep groove ball bearings



Deep groove ball bearing, radial contact, pressed steel cage, snap ring & groove on outer diameter, contact seals on both sides

Visual(s)



Product definition

d	15 mm
D	32 mm
B	9 mm
a min	1.9 mm
a max	2.06 mm
Ca min	3.02 mm
Ca max	3.18 mm
rs min	0.3 mm
rNs min	0.3 mm
D3 max	30.15 mm
b min	1.35 mm
b max	1.65 mm
r0 max	0.4 mm
D4 max	36.7 mm
f	1.12 mm
Snap ring reference	R32
Radial clearance class	C3
Mass	0.03 kg
Brand	NTN

Product performance

Dynamic load, C	5.6 kN
Static load, C0	2.83 kN
Fatigue limit load, Cu	0.13 kN
f0	13.9
Nlim (grease)	15,000 Tr/min
Min operating temperature, Tmin	-25 °C
Max operating temperature, Tmax	110 °C
Characteristic cage frequency, FTF	0.4 Hz
Characteristic rolling element frequency, BSF	4.73 Hz
Characteristic outer ring frequency, BPF0	3.59 Hz
Characteristic inner ring frequency, BPFI	5.41 Hz

Abutment dimensions

da min	17 mm
da max	19 mm
Da max	30 mm
ra max	0.3 mm
rNa max	0.3 mm
Db min	37.5 mm

Calculation factors

Equivalent dynamic radial load

P = X.Fr + Y.Fa

$\frac{f_0 F_a}{C_0}$	e	Fa / Fr ≤ e		Fa / Fr > e	
		X	Y	X	Y
0.172	0.19	1	0	0.56	2.3
0.345	0.22				1.99
0.689	0.26				1.71
1.03	0.28				1.55
1.38	0.3				1.45
2.07	0.34				1.31
3.45	0.38				1.15
5.17	0.42				1.04
6.89	0.44				1

Equivalent static radial load

Po = Xo.Fr + Yo.Fa

X_0	Y_0
0.6	0.5

For single or DT bearing arrangement :

If Po <Fr, then use Po = Fr