Technical data


6210.NR

Single row deep groove ball bearings



Deep groove ball bearing, radial contact, pressed steel cage, snap ring & groove on outer diameter, open

Visual(s)



Product definition

d	50 mm
D	90 mm
B	20 mm
d1	59.6 mm
D1	80.8 mm
a min	3.07 mm
a max	3.28 mm
Ca min	5.43 mm
Ca max	5.74 mm
rs min	1.1 mm
rNs min	0.5 mm
D3 max	86.79 mm
b min	2.7 mm
b max	3 mm
r0 max	0.6 mm
D4 max	96.5 mm
f	2.41 mm
Snap ring reference	R90
Radial clearance class	CN
Mass	0.45 kg
Brand	SNR

Product performance

Dynamic load, C	34.5 kN
Static load, C0	23.2 kN
Fatigue limit load, Cu	1.3 kN
f0	14.4
Nref	8,200 Tr/min
Nlim	12,000 Tr/min
Min operating temperature, Tmin	-40 °C
Max operating temperature, Tmax	120 °C
Characteristic cage frequency, FTF	0.41 Hz
Characteristic rolling element frequency, BSF	5.33 Hz
Characteristic outer ring frequency, BPF0	4.09 Hz
Characteristic inner ring frequency, BPFI	5.91 Hz

Abutment dimensions

da min	56.5 mm
Ce min	0 mm
Da max	83.5 mm
ra max	1 mm
rNa max	0.5 mm
Db min	98 mm

Calculation factors

Equivalent dynamic radial load

P = X.Fr + Y.Fa

$\frac{f_0 F_a}{C_0}$	e	Fa / Fr ≤ e		Fa / Fr > e	
		X	Y	X	Y
0.172	0.19	1	0	0.56	2.3
0.345	0.22				1.99
0.689	0.26				1.71
1.03	0.28				1.55
1.38	0.3				1.45
2.07	0.34				1.31
3.45	0.38				1.15
5.17	0.42				1.04
6.89	0.44				1

Equivalent static radial load

Po = Xo.Fr + Yo.Fa

X_0	Y_0
0.6	0.5

For single or DT bearing arrangement :

If Po <Fr, then use Po = Fr