


Technical data

6212.ZC3

Single row deep groove ball bearings

Deep groove ball bearing, radial contact, pressed steel cage, shield on one side

Visual(s)



Product definition

d	60 mm
D	110 mm
B	22 mm
d1	72.7 mm
D1	101.3 mm
rs min	1.5 mm
Radial clearance class	C3
Mass	0.78 kg
Brand	SNR

Product performance

Dynamic load, C	51.6 kN
Static load, C0	36.3 kN
Fatigue limit load, Cu	1.65 kN
f0	14.4
Nref	6,800 Tr/min
Nlim	9,500 Tr/min
Min operating temperature, Tmin	-40 °C
Max operating temperature, Tmax	120 °C
Characteristic cage frequency, FTF	0.41 Hz
Characteristic rolling element frequency, BSF	5.3 Hz
Characteristic outer ring frequency, BPF0	4.09 Hz
Characteristic inner ring frequency, BPFI	5.91 Hz

Abutment dimensions

da min	68 mm
da max	72.7 mm
Ce min	0 mm
Da max	102 mm
ra max	1.5 mm

Calculation factors

Equivalent dynamic radial load

P = X.Fr + Y.Fa

$\frac{f_0 F_a}{C_0}$	e	Fa / Fr ≤ e		Fa / Fr > e	
		X	Y	X	Y
0.172	0.19	1	0	0.56	2.3
0.345	0.22				1.99
0.689	0.26				1.71
1.03	0.28				1.55
1.38	0.3				1.45
2.07	0.34				1.31
3.45	0.38				1.15
5.17	0.42				1.04
6.89	0.44				1

Equivalent static radial load

Po = Xo.Fr + Yo.Fa

X_0	Y_0
0.6	0.5

For single or DT bearing arrangement :

If Po <Fr, then use Po = Fr