Technical data


6217NR

Single row deep groove ball bearings



Deep groove ball bearing, radial contact, pressed steel cage, snap ring & groove on outer diameter, open

Visual(s)



Product definition

d	85 mm
D	150 mm
B	28 mm
a min	4.65 mm
a max	4.9 mm
Ca min	7.37 mm
Ca max	7.72 mm
rs min	2 mm
rNs min	0.5 mm
D3 max	145.24 mm
b min	3.1 mm
b max	3.4 mm
r0 max	0.6 mm
D4 max	159.7 mm
f	2.82 mm
Snap ring reference	R150
Radial clearance class	CN
Mass	1.79 kg
Brand	NTN

Product performance

Dynamic load, C	83.5 kN
Static load, C0	64 kN
Fatigue limit load, Cu	2.7 kN
f0	14.7
Nlim (oil)	5,000 Tr/min
Nlim (grease)	4,200 Tr/min
Min operating temperature, Tmin	-40 °C
Max operating temperature, Tmax	120 °C
Characteristic cage frequency, FTF	0.42 Hz
Characteristic rolling element frequency, BSF	5.78 Hz
Characteristic outer ring frequency, BPF0	4.58 Hz
Characteristic inner ring frequency, BPFI	6.42 Hz

Abutment dimensions

da min	94 mm
Da max	141 mm
ra max	2 mm
rNa max	0.5 mm
Db min	162 mm

Calculation factors

Equivalent dynamic radial load

P = X.Fr + Y.Fa

$\frac{f_0 F_a}{C_0}$	e	Fa / Fr ≤ e		Fa / Fr > e	
		X	Y	X	Y
0.172	0.19	1	0	0.56	2.3
0.345	0.22				1.99
0.689	0.26				1.71
1.03	0.28				1.55
1.38	0.3				1.45
2.07	0.34				1.31
3.45	0.38				1.15
5.17	0.42				1.04
6.89	0.44				1

Equivalent static radial load

Po = Xo.Fr + Yo.Fa

X_0	Y_0
0.6	0.5

For single or DT bearing arrangement :

If Po <Fr, then use Po = Fr