
Technical data


6305ZNR

Single row deep groove ball bearings



Deep groove ball bearing, radial contact, pressed steel cage, snap ring & groove on outer diameter, shield on one side

Visual(s)



Product definition

d	25 mm
D	62 mm
B	17 mm
a min	3.07 mm
a max	3.28 mm
Ca min	4.67 mm
Ca max	4.98 mm
rs min	1.1 mm
rNs min	0.5 mm
D3 max	59.61 mm
b min	1.9 mm
b max	2.2 mm
r0 max	0.6 mm
D4 max	67.7 mm
f	1.7 mm
Snap ring reference	R62
Radial clearance class	CN
Mass	0.23 kg
Brand	NTN

Product performance

Dynamic load, C	21.2 kN
Static load, C0	10.9 kN
Fatigue limit load, Cu	0.5 kN
f0	12.6
Nlim (oil)	14,000 Tr/min
Nlim (grease)	12,000 Tr/min
Min operating temperature, Tmin	-40 °C
Max operating temperature, Tmax	120 °C
Characteristic cage frequency, FTF	0.37 Hz
Characteristic rolling element frequency, BSF	3.66 Hz
Characteristic outer ring frequency, BPF0	2.61 Hz
Characteristic inner ring frequency, BPFI	4.39 Hz

Abutment dimensions

da min	31.5 mm
Da max	55.5 mm
ra max	1 mm
rNa max	0.5 mm
Db min	68.5 mm

Calculation factors

Equivalent dynamic radial load

P = X.Fr + Y.Fa

$\frac{f_0 F_a}{C_0}$	e	Fa / Fr ≤ e		Fa / Fr > e	
		X	Y	X	Y
0.172	0.19	1	0	0.56	2.3
0.345	0.22				1.99
0.689	0.26				1.71
1.03	0.28				1.55
1.38	0.3				1.45
2.07	0.34				1.31
3.45	0.38				1.15
5.17	0.42				1.04
6.89	0.44				1

Equivalent static radial load

Po = Xo.Fr + Yo.Fa

X_0	Y_0
0.6	0.5

For single or DT bearing arrangement :

If Po <Fr, then use Po = Fr