Technical data


6306.NR

Single row deep groove ball bearings



Deep groove ball bearing, radial contact, pressed steel cage, snap ring & groove on outer diameter, open

Visual(s)



Product definition

d	30 mm
D	72 mm
B	19 mm
d1	42.4 mm
D1	62.6 mm
a min	3.07 mm
a max	3.28 mm
Ca min	4.67 mm
Ca max	4.98 mm
rs min	1.1 mm
rNs min	0.5 mm
D3 max	68.81 mm
b min	1.9 mm
b max	2.2 mm
r0 max	0.6 mm
D4 max	78.6 mm
f	1.65 mm
Snap ring reference	R72
Radial clearance class	CN
Mass	0.35 kg
Brand	SNR

Product performance

Dynamic load, C	27.9 kN
Static load, C0	15.9 kN
Fatigue limit load, Cu	0.72 kN
f0	13.1
Nref	11,000 Tr/min
Nlim	16,000 Tr/min
Min operating temperature, Tmin	-40 °C
Max operating temperature, Tmax	120 °C
Characteristic cage frequency, FTF	0.38 Hz
Characteristic rolling element frequency, BSF	3.99 Hz
Characteristic outer ring frequency, BPF0	3.05 Hz
Characteristic inner ring frequency, BPFI	4.95 Hz

Abutment dimensions

da min	36.5 mm
Ce min	0 mm
Da max	65.5 mm
ra max	1 mm
rNa max	0.5 mm
Db min	80 mm

Calculation factors

Equivalent dynamic radial load

P = X.Fr + Y.Fa

$\frac{f_0 F_a}{C_0}$	e	Fa / Fr ≤ e		Fa / Fr > e	
		X	Y	X	Y
0.172	0.19	1	0	0.56	2.3
0.345	0.22				1.99
0.689	0.26				1.71
1.03	0.28				1.55
1.38	0.3				1.45
2.07	0.34				1.31
3.45	0.38				1.15
5.17	0.42				1.04
6.89	0.44				1

Equivalent static radial load

Po = Xo.Fr + Yo.Fa

X_0	Y_0
0.6	0.5

For single or DT bearing arrangement :

If Po <Fr, then use Po = Fr