Technical data


6307LLUNR/2AS

Single row deep groove ball bearings



Deep groove ball bearing, radial contact, pressed steel cage, snap ring & groove on outer diameter, contact seals on both sides

Visual(s)



Product definition

d	35 mm
D	80 mm
B	21 mm
a min	3.07 mm
a max	3.28 mm
Ca min	4.67 mm
Ca max	4.98 mm
rs min	1.5 mm
rNs min	0.5 mm
D3 max	76.81 mm
b min	1.9 mm
b max	2.2 mm
r0 max	0.6 mm
D4 max	86.6 mm
f	1.7 mm
Snap ring reference	R80
Radial clearance class	CN
Mass	0.46 kg
Brand	NTN

Product performance

Dynamic load, C	33.5 kN
Static load, C0	19.1 kN
Fatigue limit load, Cu	0.87 kN
f0	13.1
Nlim (grease)	6,000 Tr/min
Min operating temperature, Tmin	-25 °C
Max operating temperature, Tmax	110 °C
Characteristic cage frequency, FTF	0.38 Hz
Characteristic rolling element frequency, BSF	4.03 Hz
Characteristic outer ring frequency, BPF0	3.06 Hz
Characteristic inner ring frequency, BPFI	4.94 Hz

Abutment dimensions

da min	43 mm
da max	47 mm
Da max	72 mm
ra max	1.5 mm
rNa max	0.5 mm
Db min	88 mm

Calculation factors

Equivalent dynamic radial load

P = X.Fr + Y.Fa

$\frac{f_0 F_a}{C_0}$	e	Fa / Fr ≤ e		Fa / Fr > e	
		X	Y	X	Y
0.172	0.19	1	0	0.56	2.3
0.345	0.22				1.99
0.689	0.26				1.71
1.03	0.28				1.55
1.38	0.3				1.45
2.07	0.34				1.31
3.45	0.38				1.15
5.17	0.42				1.04
6.89	0.44				1

Equivalent static radial load

Po = Xo.Fr + Yo.Fa

X_0	Y_0
0.6	0.5

For single or DT bearing arrangement :

If Po <Fr, then use Po = Fr