Technical data


6821LLU/5K

Single row deep groove ball bearings



Deep groove ball bearing, radial contact, pressed steel cage, contact seals on both sides

Visual(s)



Product definition

d	105 mm
D	130 mm
B	13 mm
rs min	1 mm
Radial clearance class	CN
Mass	0.33 kg
Brand	NTN

Product performance

Dynamic load, C	19.8 kN
Static load, C0	22 kN
Fatigue limit load, Cu	0.92 kN
f0	15.9
Nlim (grease)	2,700 Tr/min
Min operating temperature, Tmin	-25 °C
Max operating temperature, Tmax	110 °C
Characteristic cage frequency, FTF	0.47 Hz
Characteristic rolling element frequency, BSF	16.39 Hz
Characteristic outer ring frequency, BPF0	12.68 Hz
Characteristic inner ring frequency, BPFI	14.32 Hz

Abutment dimensions

da min	110 mm
Da max	125 mm
ra max	1 mm

Calculation factors

Equivalent dynamic radial load

P = X.Fr + Y.Fa

$\frac{f_0 F_a}{C_0}$	e	Fa / Fr ≤ e		Fa / Fr > e	
		X	Y	X	Y
0.172	0.19	1	0	0.56	2.3
0.345	0.22				1.99
0.689	0.26				1.71
1.03	0.28				1.55
1.38	0.3				1.45
2.07	0.34				1.31
3.45	0.38				1.15
5.17	0.42				1.04
6.89	0.44				1

Equivalent static radial load

Po = Xo.Fr + Yo.Fa

X_0	Y_0
0.6	0.5

For single or DT bearing arrangement :

If Po <Fr, then use Po = Fr