
Technical data


6920ZZ/5K

Single row deep groove ball bearings



Deep groove ball bearing, radial contact, pressed steel cage, shields on both sides

Visual(s)



Product definition

d	100 mm
D	140 mm
B	20 mm
rs min	1.1 mm
Radial clearance class	CN
Mass	0.78 kg
Brand	NTN

Product performance

Dynamic load, C	41 kN
Static load, C0	39.5 kN
Fatigue limit load, Cu	1.64 kN
f0	16.4
Nlim (grease)	4,500 Tr/min
Min operating temperature, Tmin	-20 °C
Max operating temperature, Tmax	120 °C
Characteristic cage frequency, FTF	0.45 Hz
Characteristic rolling element frequency, BSF	9.98 Hz
Characteristic outer ring frequency, BPF0	7.66 Hz
Characteristic inner ring frequency, BPFI	9.34 Hz

Abutment dimensions

da min	106.5 mm
Da max	133.5 mm
ra max	1 mm

Calculation factors

Equivalent dynamic radial load

P = X.Fr + Y.Fa

$\frac{f_0 F_a}{C_0}$	e	Fa / Fr ≤ e		Fa / Fr > e	
		X	Y	X	Y
0.172	0.19	1	0	0.56	2.3
0.345	0.22				1.99
0.689	0.26				1.71
1.03	0.28				1.55
1.38	0.3				1.45
2.07	0.34				1.31
3.45	0.38				1.15
5.17	0.42				1.04
6.89	0.44				1

Equivalent static radial load

Po = Xo.Fr + Yo.Fa

X_0	Y_0
0.6	0.5

For single or DT bearing arrangement :

If Po <Fr, then use Po = Fr