Technical datasheet

7018UCG/GNP42U3G


High precision angular contact ball bearings




High precision angular contact ball bearing, moulded polyamide cage centred on balls

ULTAGE

Visual(s)





Product definition

d	90 mm
D	140 mm
B	24 mm
d1	106.9 mm
d2	103 mm
D1	123.2 mm
D2	131.1 mm
a	27.5 mm
Contact angle α	15 °
rs min	1.5 mm
r1s min	1 mm
f0	15.7
Precision class	P42
Mass	1.17 kg
Brand	NTN

Product performance

Dynamic load, C	74 kN
Static load, C0	72.5 kN
Nlim (oil)	16,300 rpm
Nlim (grease)	10,200 rpm
Preload level	GN
Preload value	0.44 kN
Axial rigidity	117.4 N/µm
Radial rigidity	675 N/µm
Min operating temperature, Tmin	-20 °C
Max operating temperature, Tmax	120 °C
Characteristic cage frequency, FTF	0.44 Hz
Characteristic rolling element frequency, BSF	7.5 Hz
Characteristic outer ring frequency, BPF0	9.17 Hz
Characteristic inner ring frequency, BPFI	11.83 Hz

Abutment dimensions

da min	98.5 mm
Da max	131.5 mm
Db max	134.5 mm
r1a max	1 mm
ra max	1.5 mm
D6	106.9 mm

Calculation factors

Equivalent dynamic radial load

P = X.Fr + Y.Fa

Series				e	Single or DT bearing arrangement				DB or DF arrangement			
					Fa / Fr ≤ e		Fa / Fr > e		Fa / Fr ≤ e		Fa / Fr > e	
					X	Y	X	Y	X	Y	X	Y
70 (NTN & SNR) 72 (NTN & SNR) 78 (NTN) 79 (NTN) 719 (SNR)	15°	0.178	0.38	1	0	0.44	1.47	1	1.65	0.72	2.39
		0.357	0.4				1.4		1.57		2.28
		0.714	0.43				1.3		1.46		2.11
		1.07	0.46				1.23		1.38		2
		1.43	0.47				1.19		1.34		1.93
		2.14	0.5				1.12		1.26		1.82
		3.57	0.55				1.02		1.14		1.66
		5.35	0.56						1.12		1.63
		7.14	0.56				1		1.12		1.63
	25°		0.68				0.41	0.87	0.92	0.67	1.41
	30°		0.8				0.39	0.76	0.78	0.63	1.24

Equivalent static radial load

Po = Xo.Fr + Yo.Fa

Series		Single or DT bearing arrangement		DB or DF arrangement	
		X_0	Y_0	X_0	Y_0
70 (NTN & SNR) 72 (NTN & SNR) 78 (NTN) 79 (NTN) 719 (SNR)	15°	0.5	0.46	1	0.92
	25°		0.38		0.76
	30°		0.33		0.66

For single or DT bearing arrangement :

If Po <Fr, then use Po = Fr