Technical datasheet

7917UADG/GNP42U3G


High precision angular contact ball bearings




High precision angular contact ball bearing, moulded polyamide cage centred on balls

ULTAGE

Visual(s)





Product definition

d	85 mm
D	120 mm
B	18 mm
d1	96.9 mm
d2	94.3 mm
D1	108.1 mm
D2	113.5 mm
a	33 mm
Contact angle α	25 °
rs min	1.1 mm
r1s min	0.6 mm
f0	16.6
Precision class	P42
Mass	0.54 kg
Brand	NTN

Product performance

Dynamic load, C	38.5 kN
Static load, C0	41.5 kN
Nlim (oil)	16,000 rpm
Nlim (grease)	9,900 rpm
Preload level	GN
Preload value	0.39 kN
Axial rigidity	233.8 N/µm
Radial rigidity	500 N/µm
Min operating temperature, Tmin	-20 °C
Max operating temperature, Tmax	120 °C
Characteristic cage frequency, FTF	0.45 Hz
Characteristic rolling element frequency, BSF	9.85 Hz
Characteristic outer ring frequency, BPF0	11.81 Hz
Characteristic inner ring frequency, BPFI	14.19 Hz

Abutment dimensions

da min	92 mm
Da max	113 mm
Db max	115.5 mm
r1a max	0.6 mm
ra max	1 mm
D6	97.4 mm

Calculation factors

Equivalent dynamic radial load

P = X.Fr + Y.Fa

Series				e	Single or DT bearing arrangement				DB or DF arrangement			
					Fa / Fr ≤ e		Fa / Fr > e		Fa / Fr ≤ e		Fa / Fr > e	
					X	Y	X	Y	X	Y	X	Y
70 (NTN & SNR) 72 (NTN & SNR) 78 (NTN) 79 (NTN) 719 (SNR)		15°	0.178	0.38	1	0	0.44	1.47	1	1.65	0.72	2.39
			0.357	0.4				1.4		1.57		2.28
			0.714	0.43				1.3		1.46		2.11
			1.07	0.46				1.23		1.38		2
			1.43	0.47				1.19		1.34		1.93
			2.14	0.5				1.12		1.26		1.82
			3.57	0.55				1.02		1.14		1.66
			5.35	0.56						1.12		1.63
			7.14	0.56				1		1.12		1.63
		25°		0.68			0.41	0.87		0.92	0.67	1.41
		30°		0.8			0.39	0.76		0.78	0.63	1.24

Equivalent static radial load

Po = Xo.Fr + Yo.Fa

Series			Single or DT bearing arrangement		DB or DF arrangement	
			X_0	Y_0	X_0	Y_0
70 (NTN & SNR) 72 (NTN & SNR) 78 (NTN) 79 (NTN) 719 (SNR)		15°	0.5	0.46	1	0.92
		25°		0.38		0.76
		30°		0.33		0.66

For single or DT bearing arrangement :

If Po <Fr, then use Po = Fr