
Technical data


NJ1006G1

Single row cylindrical roller bearings

Single row cylindrical roller bearing, single direction for axial loads, separable, brass cage.

Visual(s)





Product definition

d	30 mm
D	55 mm
B	13 mm
E	48.5 mm
F	36.5 mm
d1	38.9 mm
rs min	1 mm
r1s min	0.6 mm
Radial clearance class	CN
Mass (without HJ ring)	0.13 kg
Brand	NTN

Product performance

Dynamic load, C	19.7 kN
Static load, C0	19.6 kN
Fatigue limit load, Cu	2.39 kN
Nlim (oil)	16,000 Tr/min
Nlim (grease)	14,000 Tr/min
Min operating temperature, Tmin	-40 °C
Max operating temperature, Tmax	120 °C
Characteristic cage frequency, FTF	0.43 Hz
Characteristic rolling element frequency, BSF	6.94 Hz
Characteristic outer ring frequency, BPF0	6.87 Hz
Characteristic inner ring frequency, BPFI	9.13 Hz

Abutment dimensions

da min	35 mm
da max	35 mm
dc min	39.5 mm
Da max	50 mm
ra max	1 mm

Calculation factors

Equivalent dynamic radial load

$P = Fr$

Equivalent static radial load

$P_0 = Fr$