
# Technical data

## NJ2209

Single row cylindrical roller bearings

Single row cylindrical roller bearing, single direction for axial loads, separable, pressed steel cage.

## Visual(s)




## Product definition

| | |
|---|---|
| **d** | 45 mm |
| **D** | 85 mm |
| **B** | 23 mm |
| **E** | 75 mm |
| **F** | 55 mm |
| **d1** | 59 mm |
| **rs min** | 1.1 mm |
| **r1s min** | 1.1 mm |
| **Radial clearance class** | CN |
| **Mass (without HJ ring)** | 0.57 kg |
| **Brand** | NTN |

## Product performance

| | |
|---|---|
| **Dynamic load, C** | 61.5 kN |
| **Static load, C0** | 68 kN |
| **Fatigue limit load, Cu** | 8.3 kN |
| **Nlim (oil)** | 9,000 Tr/min |
| **Nlim (grease)** | 7,600 Tr/min |
| **Min operating temperature, Tmin** | -40 °C |
| **Max operating temperature, Tmax** | 120 °C |
| **Characteristic cage frequency, FTF** | 0.42 Hz |
| **Characteristic rolling element frequency, BSF** | 6.35 Hz |
| **Characteristic outer ring frequency, BPF0** | 5.92 Hz |
| **Characteristic inner ring frequency, BPFI** | 8.08 Hz |

## Abutment dimensions

| | |
|---|---|
| **da min** | 51.5 mm |
| **da max** | 54 mm |
| **dc min** | 61 mm |
| **Da max** | 78.5 mm |
| **ra max** | 1 mm |

## Calculation factors

Equivalent dynamic radial load

$P = Fr$

Equivalent static radial load

$P_0 = Fr$