Technical datasheet


NJ2211EAT2X


Single row cylindrical roller bearings

Single row cylindrical roller bearing, single direction for axial loads, separable, polyamide cage.

ULTAGE

Visual(s)





Product definition

d	55 mm
D	100 mm
B	25 mm
E	90 mm
F	66 mm
d1	70.8 mm
D1	85.6 mm
rs min	1.5 mm
r1s min	1.1 mm
Radial clearance class	CN
Mass (without HJ ring)	0.82 kg
Brand	NTN

Product performance

Dynamic load, C	120 kN
Static load, C0	122 kN
Nlim (oil)	7,900 rpm
Nlim (grease)	5,600 rpm
Min operating temperature, Tmin	-20 °C
Max operating temperature, Tmax	120 °C
Characteristic cage frequency, FTF	0.42 Hz
Characteristic rolling element frequency, BSF	6.35 Hz
Characteristic outer ring frequency, BPF0	7.19 Hz
Characteristic inner ring frequency, BPFI	9.81 Hz

Abutment dimensions

da min	63 mm
dc min	73 mm
Da max	92 mm
ra max	1.5 mm
r1a max	1 mm

Calculation factors

Equivalent dynamic radial load

$P = Fr$

Equivalent static radial load

$Po = Fr$