Technical data


NU2304ET2X

Single row cylindrical roller bearings



Single row cylindrical roller bearing, floating, separable, polyamide cage

Visual(s)



Product definition

d	20 mm
D	52 mm
B	21 mm
E	45.5 mm
F	27.5 mm
rs min	1.1 mm
r1s min	0.6 mm
Radial clearance class	CN
Mass (without HJ ring)	0.22 kg
Brand	NTN

Product performance

Dynamic load, C	42 kN
Static load, C0	39 kN
Fatigue limit load, Cu	4.75 kN
Nlim (oil)	14,000 Tr/min
Nlim (grease)	12,000 Tr/min
Min operating temperature, Tmin	-20 °C
Max operating temperature, Tmax	120 °C
Characteristic cage frequency, FTF	0.38 Hz
Characteristic rolling element frequency, BSF	3.81 Hz
Characteristic outer ring frequency, BPF0	3.77 Hz
Characteristic inner ring frequency, BPFI	6.23 Hz

Abutment dimensions

da min	24 mm
da max	27 mm
db min	30 mm
Da max	45.5 mm
ra max	1 mm
r1a max	0.6 mm

Calculation factors

Equivalent dynamic radial load

P = Fr

Equivalent static radial load

Po = Fr