# Technical data

## 10X22208EAW33EE


Double row spherical roller bearings



Spherical roller bearing, pressed steel cage, groove and lubrication holes on outer ring, non ISO width, contact seals on both sides

ULTAGE

## Visual(s)




## Product definition

| | |
|---|---|
| **d** | 40 mm |
| **D** | 80 mm |
| **B** | 28 mm |
| **d2** | 47.8 mm |
| **D1** | 73.9 mm |
| **rs min** | 1.1 mm |
| **Number of lubrication holes** | 3 |
| **b** | 5.4 mm |
| **k** | 2.5 mm |
| **Associated sleeve reference** | P0 |
| **e** | 0.27 |
| **Y1** | 2.47 |
| **Y2** | 3.68 |
| **Y0** | 2.41 |
| **Radial clearance class** | CN |
| **Mass** | 0.62 kg |
| **Brand** | SNR |

## Product performance

| | |
|---|---|
| **Dynamic load, C** | 116 kN |
| **Static load, C0** | 105 kN |
| **Fatigue limit load, Cu** | 10.9 kN |
| **Nref** | 116 Tr/min |
| **Nlim** | 2,300 Tr/min |
| **Min operating temperature, Tmin** | -20 °C |
| **Max operating temperature, Tmax** | 120 °C |
| **Characteristic cage frequency, FTF** | 0.42 Hz |
| **Characteristic rolling element frequency, BSF** | 5.62 Hz |
| **Characteristic outer ring frequency, BPF0** | 6.64 Hz |
| **Characteristic inner ring frequency, BPFI** | 9.36 Hz |

## Abutment dimensions

| | |
|---|---|
| **da min** | 47 mm |
| **da max** | 47.8 mm |
| **db min** | 47.8 mm |
| **Da max** | 73.9 mm |
| **ra max** | 1 mm |

## Calculation factors

**Equivalent dynamic radial load**

$P = X.Fr + Y.Fa$

| Fa / Fr ≤ e | | Fa / Fr > e | |
|---|---|---|---|
| X | Y | X | Y |
| 1 | Y1 | 0.67 | Y2 |

**Equivalent static radial load**

$P_0 = X_0.Fr + Y_0.Fa$

| $X_0$ | $Y_0$ |
|---|---|
| 1 | Y0 |

The values for e, Y1, Y2 and Y0 are shown in the above table .