Technical data

10X22215EAKW33EEC3


Double row spherical roller bearings



Spherical roller bearing, pressed steel cage, groove and lubrication holes on outer ring, tapered bore 1:12, non ISO width, contact seals on both sides

ULTAGE

Visual(s)



Product definition

d	75 mm
D	130 mm
B	38 mm
d2	85.1 mm
D1	121.6 mm
rs min	1.5 mm
Number of lubrication holes	3
b	7.4 mm
k	3.5 mm
Associated sleeve reference	H315E
e	0.22
Y1	3.14
Y2	4.67
Y0	3.07
Radial clearance class	C3
Mass	1.87 kg
Brand	SNR

Product performance

Dynamic load, C	244 kN
Static load, C0	249 kN
Fatigue limit load, Cu	30.3 kN
Nref	244 Tr/min
Nlim	1,300 Tr/min
Min operating temperature, Tmin	-20 °C
Max operating temperature, Tmax	120 °C
Characteristic cage frequency, FTF	0.43 Hz
Characteristic rolling element frequency, BSF	6.71 Hz
Characteristic outer ring frequency, BPF0	8.13 Hz
Characteristic inner ring frequency, BPFI	10.87 Hz

Abutment dimensions

da min	84 mm
da max	85.1 mm
db min	80 mm
Ce min	5 mm
Da max	121.6 mm
ra max	1.5 mm

Calculation factors

Equivalent dynamic radial load

$P = X.Fr + Y.Fa$

$Fa/Fr \leq e$		$Fa/Fr > e$	
X	Y	X	Y
1	Y1	0.67	Y2

Equivalent static radial load

$P_0 = X_0.Fr + Y_0.Fa$

X_0	Y_0
1	Y0

The values for e, Y1, Y2 and Y0 are shown in the above table .