Technical data

21306.VC3


Double row spherical roller bearings

Spherical roller bearing, pressed steel cage

ULTAGE



Visual(s)



Product definition

d	30 mm
D	72 mm
B	19 mm
d2	40.8 mm
D1	59.7 mm
rs min	1.1 mm
Number of lubrication holes	0
b	2 mm
k	0 mm
Associated sleeve reference	P0
e	0.28
Y1	2.45
Y2	3.64
Y0	2.39
Radial clearance class	C3
Mass	0.39 kg
Brand	SNR

Product performance

Dynamic load, C	6 kN
Static load, C0	50.4 kN
Fatigue limit load, Cu	6.6 kN
Nref	7,800 Tr/min
Nlim	12,000 Tr/min
Min operating temperature, Tmin	-40 °C
Max operating temperature, Tmax	200 °C
Characteristic cage frequency, FTF	0.4 Hz
Characteristic rolling element frequency, BSF	4.97 Hz
Characteristic outer ring frequency, BPF0	4.86 Hz
Characteristic inner ring frequency, BPFI	7.14 Hz

Abutment dimensions

da min	37 mm
da max	1 mm
Da max	65 mm
ra max	1 mm

Calculation factors

Equivalent dynamic radial load

$P = X.Fr + Y.Fa$

$Fa/Fr \leq e$		$Fa/Fr > e$	
X	Y	X	Y
1	Y1	0.67	Y2

Equivalent static radial load

$P_0 = X_0.Fr + Y_0.Fa$

X_0	Y_0
1	Y0

The values for e, Y1, Y2 and Y0 are shown in the above table .