Technical data

21312.VC3


Double row spherical roller bearings

Spherical roller bearing, pressed steel cage

ULTAGE



Visual(s)



Product definition

d	60 mm
D	130 mm
B	31 mm
d2	79.5 mm
D1	109.9 mm
rs min	2.1 mm
Number of lubrication holes	0
b	2 mm
k	0 mm
Associated sleeve reference	P0
e	0.24
Y1	2.82
Y2	4.19
Y0	2.75
Radial clearance class	C3
Mass	1.99 kg
Brand	SNR

Product performance

Dynamic load, C	10.3 kN
Static load, C0	179 kN
Fatigue limit load, Cu	23.7 kN
Nref	4,700 Tr/min
Nlim	6,400 Tr/min
Min operating temperature, Tmin	-40 °C
Max operating temperature, Tmax	200 °C
Characteristic cage frequency, FTF	0.42 Hz
Characteristic rolling element frequency, BSF	5.92 Hz
Characteristic outer ring frequency, BPF0	6.28 Hz
Characteristic inner ring frequency, BPFI	8.72 Hz

Abutment dimensions

da min	72 mm
da max	2 mm
Da max	118 mm
ra max	2 mm

Calculation factors

Equivalent dynamic radial load

$P = X.Fr + Y.Fa$

$Fa/Fr \leq e$		$Fa/Fr > e$	
X	Y	X	Y
1	Y1	0.67	Y2

Equivalent static radial load

$P_0 = X_0.Fr + Y_0.Fa$

X_0	Y_0
1	Y0

The values for e, Y1, Y2 and Y0 are shown in the above table .