Technical data

22206EMW33C4


Double row spherical roller bearings




Spherical roller bearing, one-piece machined cage, groove and lubrication holes on outer ring

ULTAGE

Visual(s)





Product definition

d	30 mm
D	62 mm
B	20 mm
D1	54.3 mm
rs min	1 mm
Number of lubrication holes	3
b	4.4 mm
k	2 mm
Associated sleeve reference	P0
e	0.31
Y1	2.15
Y2	3.2
Y0	2.1
Radial clearance class	C4
Mass	0.28 kg
Brand	SNR

Product performance

Dynamic load, C	71.9 kN
Static load, C0	60.2 kN
Fatigue limit load, Cu	6.1 kN
Nref	11,000 Tr/min
Nlim	14,000 Tr/min
Min operating temperature, Tmin	-40 °C
Max operating temperature, Tmax	200 °C
Characteristic cage frequency, FTF	0.41 Hz
Characteristic rolling element frequency, BSF	5.25 Hz
Characteristic outer ring frequency, BPF0	5.74 Hz
Characteristic inner ring frequency, BPFI	8.26 Hz

Abutment dimensions

da min	35.6 mm
da max	1 mm
Da max	56.4 mm
ra max	1 mm

Calculation factors

Equivalent dynamic radial load

$P = X.Fr + Y.Fa$

$Fa/Fr \leq e$		$Fa/Fr > e$	
X	Y	X	Y
1	Y1	0.67	Y2

Equivalent static radial load

$Po = Xo.Fr + Yo.Fa$

X_0	Y_0
1	Y0

The values for e, Y1, Y2 and Y0 are shown in the above table .