Technical data

22214EAKW33C4


Double row spherical roller bearings



Spherical roller bearing, pressed steel cage, groove and lubrication holes on outer ring, tapered bore 1:12

ULTAGE

Visual(s)



Product definition

d	70 mm
D	125 mm
B	31 mm
d2	84.1 mm
D1	112.7 mm
rs min	1.5 mm
Number of lubrication holes	3
b	7.4 mm
k	3.5 mm
Associated sleeve reference	H314
e	0.22
Y1	3.01
Y2	4.48
Y0	2.94
Radial clearance class	C4
Mass	1.52 kg
Brand	SNR

Product performance

Dynamic load, C	235 kN
Static load, C0	240 kN
Fatigue limit load, Cu	28.8 kN
Nref	4,900 Tr/min
Nlim	6,500 Tr/min
Min operating temperature, Tmin	-40 °C
Max operating temperature, Tmax	200 °C
Characteristic cage frequency, FTF	0.43 Hz
Characteristic rolling element frequency, BSF	6.57 Hz
Characteristic outer ring frequency, BPF0	8.1 Hz
Characteristic inner ring frequency, BPFI	10.9 Hz

Abutment dimensions

da min	79 mm
da max	1.5 mm
db min	75 mm
Ce min	9 mm
Da max	116 mm
ra max	1.5 mm

Calculation factors

Equivalent dynamic radial load

$P = X.Fr + Y.Fa$

$Fa/Fr \leq e$		$Fa/Fr > e$	
X	Y	X	Y
1	Y1	0.67	Y2

Equivalent static radial load

$P_0 = X_0.Fr + Y_0.Fa$

X_0	Y_0
1	Y0

The values for e, Y1, Y2 and Y0 are shown in the above table .