Technical data

22218EMW33C4


Double row spherical roller bearings




Spherical roller bearing, one-piece machined cage, groove and lubrication holes on outer ring

ULTAGE

Visual(s)





Product definition

d	90 mm
D	160 mm
B	40 mm
D1	143.2 mm
rs min	2 mm
Number of lubrication holes	3
b	10.2 mm
k	4.5 mm
Associated sleeve reference	P0
e	0.23
Y1	2.9
Y2	4.31
Y0	2.83
Radial clearance class	C4
Mass	3.3 kg
Brand	SNR

Product performance

Dynamic load, C	384 kN
Static load, C0	398 kN
Fatigue limit load, Cu	43.1 kN
Nref	3,900 Tr/min
Nlim	5,100 Tr/min
Min operating temperature, Tmin	-40 °C
Max operating temperature, Tmax	200 °C
Characteristic cage frequency, FTF	0.42 Hz
Characteristic rolling element frequency, BSF	6.24 Hz
Characteristic outer ring frequency, BPF0	7.61 Hz
Characteristic inner ring frequency, BPFI	10.39 Hz

Abutment dimensions

da min	101 mm
da max	2 mm
Da max	149 mm
ra max	2 mm

Calculation factors

Equivalent dynamic radial load

$P = X.Fr + Y.Fa$

$Fa/Fr \leq e$		$Fa/Fr > e$	
X	Y	X	Y
1	Y1	0.67	Y2

Equivalent static radial load

$P_0 = X_0.Fr + Y_0.Fa$

X_0	Y_0
1	Y0

The values for e, Y1, Y2 and Y0 are shown in the above table .