Technical data

22220.EF800


Double row spherical roller bearings



Spherical roller bearing for vibratory applications, one-piece machined cage, groove and lubrication holes on outer ring, special C4 class clearance

ULTAGE

Visual(s)



Product definition

d	100 mm
D	180 mm
B	46 mm
d2	118.2 mm
D1	160.8 mm
rs min	2.1 mm
Number of lubrication holes	3
b	11.2 mm
k	5 mm
Associated sleeve reference	P0spé
e	0.24
Y1	2.84
Y2	4.23
Y0	2.78
Radial clearance class	C4 Special
Mass	4.82 kg
Brand	SNR

Product performance

Dynamic load, C	472 kN
Static load, C0	495 kN
Fatigue limit load, Cu	52.6 kN
Nref	3,600 Tr/min
Nlim	4,600 Tr/min
Min operating temperature, Tmin	-40 °C
Max operating temperature, Tmax	200 °C
Characteristic cage frequency, FTF	0.42 Hz
Characteristic rolling element frequency, BSF	6.23 Hz
Characteristic outer ring frequency, BPF0	7.61 Hz
Characteristic inner ring frequency, BPFI	10.39 Hz

Abutment dimensions

da min	112 mm
da max	2 mm
Da max	168 mm
ra max	2 mm

Calculation factors

Equivalent dynamic radial load

$P = X.Fr + Y.Fa$

$Fa / Fr \leq e$		$Fa / Fr > e$	
X	Y	X	Y
1	Y1	0.67	Y2

Equivalent static radial load

$Po = Xo.Fr + Yo.Fa$

X_0	Y_0
1	Y0

The values for e, Y1, Y2 and Y0 are shown in the above table .