Technical data

22230EAKW33C4


Double row spherical roller bearings



Spherical roller bearing, pressed steel cage, groove and lubrication holes on outer ring, tapered bore 1:12

ULTAGE

Visual(s)



Product definition

d	150 mm
D	270 mm
B	73 mm
d2	177.3 mm
D1	241.1 mm
rs min	3 mm
Number of lubrication holes	3
b	15.3 mm
k	7 mm
Associated sleeve reference	H3130
e	0.25
Y1	2.74
Y2	4.08
Y0	2.68
Radial clearance class	C4
Mass	17.6 kg
Brand	SNR

Product performance

Dynamic load, C	1,080 kN
Static load, C0	1,220 kN
Fatigue limit load, Cu	106 kN
Nref	2,200 Tr/min
Nlim	3,000 Tr/min
Min operating temperature, Tmin	-40 °C
Max operating temperature, Tmax	200 °C
Characteristic cage frequency, FTF	0.42 Hz
Characteristic rolling element frequency, BSF	6.18 Hz
Characteristic outer ring frequency, BPF0	7.6 Hz
Characteristic inner ring frequency, BPFI	10.4 Hz

Abutment dimensions

da min	164 mm
da max	2.5 mm
db min	160 mm
Ce min	15 mm
Da max	256 mm
ra max	2.5 mm

Calculation factors

Equivalent dynamic radial load

$P = X.Fr + Y.Fa$

$Fa/Fr \leq e$		$Fa/Fr > e$	
X	Y	X	Y
1	Y1	0.67	Y2

Equivalent static radial load

$P_0 = X_0.Fr + Y_0.Fa$

X_0	Y_0
1	Y0

The values for e, Y1, Y2 and Y0 are shown in the above table .