Technical data

22238.EMKW33


Double row spherical roller bearings



Spherical roller bearing, one-piece machined cage, groove and lubrication holes on outer ring, tapered bore 1:12

ULTAGE

Visual(s)



Product definition

d	190 mm
D	340 mm
B	92 mm
D1	304.8 mm
rs min	4 mm
Number of lubrication holes	3
b	19.6 mm
k	9 mm
Associated sleeve reference	H3138
e	0.25
Y1	2.74
Y2	4.08
Y0	2.68
Radial clearance class	CN
Mass	35 kg
Brand	SNR

Product performance

Dynamic load, C	1,620 kN
Static load, C0	1,870 kN
Fatigue limit load, Cu	159 kN
Nref	1,600 Tr/min
Nlim	2,400 Tr/min
Min operating temperature, Tmin	-40 °C
Max operating temperature, Tmax	200 °C
Characteristic cage frequency, FTF	0.42 Hz
Characteristic rolling element frequency, BSF	6.11 Hz
Characteristic outer ring frequency, BPF0	7.58 Hz
Characteristic inner ring frequency, BPFI	10.42 Hz

Abutment dimensions

da min	207 mm
da max	3 mm
db min	202 mm
Ce min	21 mm
Da max	323 mm
ra max	3 mm

Calculation factors

Equivalent dynamic radial load

$P = X.Fr + Y.Fa$

$Fa/Fr \leq e$		$Fa/Fr > e$	
X	Y	X	Y
1	Y1	0.67	Y2

Equivalent static radial load

$P_0 = X_0.Fr + Y_0.Fa$

X_0	Y_0
1	Y0

The values for e, Y1, Y2 and Y0 are shown in the above table .