Technical data

22244EMW33C4


Double row spherical roller bearings




Spherical roller bearing, one-piece machined cage, groove and lubrication holes on outer ring

ULTAGE

Visual(s)





Product definition

d	220 mm
D	400 mm
B	108 mm
D1	357.7 mm
rs min	4 mm
Number of lubrication holes	3
b	20.6 mm
k	11 mm
Associated sleeve reference	P0
e	0.25
Y1	2.74
Y2	4.08
Y0	2.68
Radial clearance class	C4
Mass	59.47 kg
Brand	SNR

Product performance

Dynamic load, C	2,210 kN
Static load, C0	2,690 kN
Fatigue limit load, Cu	213 kN
Nref	1,300 Tr/min
Nlim	2,000 Tr/min
Min operating temperature, Tmin	-40 °C
Max operating temperature, Tmax	200 °C
Characteristic cage frequency, FTF	0.42 Hz
Characteristic rolling element frequency, BSF	6.35 Hz
Characteristic outer ring frequency, BPF0	8.06 Hz
Characteristic inner ring frequency, BPFI	10.94 Hz

Abutment dimensions

da min	237 mm
da max	3 mm
Da max	383 mm
ra max	3 mm

Calculation factors

Equivalent dynamic radial load

$P = X.Fr + Y.Fa$

$Fa/Fr \leq e$		$Fa/Fr > e$	
X	Y	X	Y
1	Y1	0.67	Y2

Equivalent static radial load

$P_0 = X_0.Fr + Y_0.Fa$

X_0	Y_0
1	Y0

The values for e, Y1, Y2 and Y0 are shown in the above table .