Technical data

22313.EAW33


Double row spherical roller bearings


Spherical roller bearing, pressed steel cage, groove and lubrication holes on outer ring

ULTAGE



Visual(s)





Product definition

d	65 mm
D	140 mm
B	48 mm
d2	81.3 mm
D1	121.2 mm
rs min	2.1 mm
Number of lubrication holes	3
b	9.2 mm
k	4 mm
Associated sleeve reference	P0
e	0.33
Y1	2.06
Y2	3.06
Y0	2.01
Radial clearance class	CN
Mass	3.41 kg
Brand	SNR

Product performance

Dynamic load, C	369 kN
Static load, C0	343 kN
Fatigue limit load, Cu	33.9 kN
Nref	4,000 Tr/min
Nlim	4,800 Tr/min
Min operating temperature, Tmin	-40 °C
Max operating temperature, Tmax	200 °C
Characteristic cage frequency, FTF	0.4 Hz
Characteristic rolling element frequency, BSF	4.75 Hz
Characteristic outer ring frequency, BPF0	5.62 Hz
Characteristic inner ring frequency, BPFI	8.38 Hz

Abutment dimensions

da min	77 mm
da max	2 mm
Da max	128 mm
ra max	2 mm

Calculation factors

Equivalent dynamic radial load

$P = X.Fr + Y.Fa$

$Fa/Fr \leq e$		$Fa/Fr > e$	
X	Y	X	Y
1	Y1	0.67	Y2

Equivalent static radial load

$P_0 = X_0.Fr + Y_0.Fa$

X_0	Y_0
1	Y0

The values for e, Y1, Y2 and Y0 are shown in the above table .