Technical data


22316.E.F801

Double row spherical roller bearings

Spherical roller bearing for vibratory applications, one-piece machined cage, groove and lubrication holes on outer ring, special C3 class clearance

ULTAGE

Visual(s)



Product definition

d	80 mm
D	170 mm
B	58 mm
d2	98.1 mm
D1	147.4 mm
rs min	2.1 mm
Number of lubrication holes	3
b	10.5 mm
k	5 mm
Associated sleeve reference	P0spé
e	0.34
Y1	2
Y2	2.98
Y0	1.96
Radial clearance class	C3 Special
Mass	6.2 kg
Brand	SNR

Product performance

Dynamic load, C	541 kN
Static load, C0	522 kN
Fatigue limit load, Cu	47.3 kN
Nref	3,400 Tr/min
Nlim	3,900 Tr/min
Min operating temperature, Tmin	-40 °C
Max operating temperature, Tmax	200 °C
Characteristic cage frequency, FTF	0.4 Hz
Characteristic rolling element frequency, BSF	4.74 Hz
Characteristic outer ring frequency, BPF0	5.62 Hz
Characteristic inner ring frequency, BPFI	8.38 Hz

Abutment dimensions

da min	92 mm
da max	2 mm
Da max	158 mm
ra max	2 mm

Calculation factors

Equivalent dynamic radial load

$P = X.Fr + Y.Fa$

$Fa / Fr \leq e$		$Fa / Fr > e$	
X	Y	X	Y
1	Y1	0.67	Y2

Equivalent static radial load

$Po = Xo.Fr + Yo.Fa$

X_0	Y_0
1	Y0

The values for e, Y1, Y2 and Y0 are shown in the above table .