Technical data


22318.EMKC3


Double row spherical roller bearings

Spherical roller bearing, one-piece machined cage, tapered bore 1:12

ULTAGE

Visual(s)





Product definition

d	90 mm
D	190 mm
B	64 mm
d2	110.1 mm
D1	165.1 mm
rs min	3 mm
Number of lubrication holes	0
b	2 mm
k	0 mm
Associated sleeve reference	H2318
e	0.33
Y1	2.06
Y2	3.07
Y0	2.01
Radial clearance class	C3
Mass	8.53 kg
Brand	SNR

Product performance

Dynamic load, C	668 kN
Static load, C0	652 kN
Fatigue limit load, Cu	58 kN
Nref	3,000 Tr/min
Nlim	3,500 Tr/min
Min operating temperature, Tmin	-40 °C
Max operating temperature, Tmax	200 °C
Characteristic cage frequency, FTF	0.4 Hz
Characteristic rolling element frequency, BSF	4.68 Hz
Characteristic outer ring frequency, BPF0	5.6 Hz
Characteristic inner ring frequency, BPFI	8.4 Hz

Abutment dimensions

da min	104 mm
da max	2.5 mm
db min	100 mm
Ce min	7 mm
Da max	176 mm
ra max	2.5 mm

Calculation factors

Equivalent dynamic radial load

$P = X.Fr + Y.Fa$

$Fa/Fr \leq e$		$Fa/Fr > e$	
X	Y	X	Y
1	Y1	0.67	Y2

Equivalent static radial load

$P_0 = X_0.Fr + Y_0.Fa$

X_0	Y_0
1	Y0

The values for e, Y1, Y2 and Y0 are shown in the above table .