Technical data

22320.EAW33C4


Double row spherical roller bearings


Spherical roller bearing, pressed steel cage, groove and lubrication holes on outer ring

ULTAGE



Visual(s)





Product definition

d	100 mm
D	215 mm
B	73 mm
d2	126.7 mm
D1	186.7 mm
rs min	3 mm
Number of lubrication holes	3
b	13.3 mm
k	6 mm
Associated sleeve reference	P0
e	0.34
Y1	1.98
Y2	2.94
Y0	1.93
Radial clearance class	C4
Mass	12.47 kg
Brand	SNR

Product performance

Dynamic load, C	827 kN
Static load, C0	844 kN
Fatigue limit load, Cu	72.4 kN
Nref	2,600 Tr/min
Nlim	3,100 Tr/min
Min operating temperature, Tmin	-40 °C
Max operating temperature, Tmax	200 °C
Characteristic cage frequency, FTF	0.4 Hz
Characteristic rolling element frequency, BSF	4.96 Hz
Characteristic outer ring frequency, BPF0	6.08 Hz
Characteristic inner ring frequency, BPFI	8.92 Hz

Abutment dimensions

da min	114 mm
da max	2.5 mm
Da max	201 mm
ra max	2.5 mm

Calculation factors

Equivalent dynamic radial load

$P = X.Fr + Y.Fa$

Fa / Fr ≤ e		Fa / Fr > e	
X	Y	X	Y
1	Y1	0.67	Y2

Equivalent static radial load

$P_0 = X_0.Fr + Y_0.Fa$

X_0	Y_0
1	Y0

The values for e, Y1, Y2 and Y0 are shown in the above table .