Technical data


23032.EMW33C4

Double row spherical roller bearings

Spherical roller bearing, one-piece machined cage, groove and lubrication holes on outer ring

ULTAGE

Visual(s)



Product definition

d	160 mm
D	240 mm
B	60 mm
D1	220.2 mm
rs min	2.1 mm
Number of lubrication holes	3
b	10.5 mm
k	5 mm
Associated sleeve reference	P0
e	0.21
Y1	3.2
Y2	4.77
Y0	3.13
Radial clearance class	C4
Mass	9.58 kg
Brand	SNR

Product performance

Dynamic load, C	748 kN
Static load, C0	1,000 kN
Fatigue limit load, Cu	85.1 kN
Nref	2,400 Tr/min
Nlim	2,900 Tr/min
Min operating temperature, Tmin	-40 °C
Max operating temperature, Tmax	200 °C
Characteristic cage frequency, FTF	0.45 Hz
Characteristic rolling element frequency, BSF	8.99 Hz
Characteristic outer ring frequency, BPF0	11.14 Hz
Characteristic inner ring frequency, BPFI	13.86 Hz

Abutment dimensions

da min	170.2 mm
da max	2 mm
Da max	229.8 mm
ra max	2 mm

Calculation factors

Equivalent dynamic radial load

$P = X.Fr + Y.Fa$

$Fa/Fr \leq e$		$Fa/Fr > e$	
X	Y	X	Y
1	Y1	0.67	Y2

Equivalent static radial load

$P_0 = X_0.Fr + Y_0.Fa$

X_0	Y_0
1	Y0

The values for e, Y1, Y2 and Y0 are shown in the above table .